

H.M.I.S. RATING			
Health	1		
Flammability	0		
Reactivity	0		
Protective Equip.	Е		

Material Safety Data Sheet – OSHA 174 Material Safety Data Sheet US Dep

May be used to comply with OSHA's Hazard communication Standard, 29 CFR 1910.1200. Standard must be consulted for specific requirements.

US Department of Labor

Occupational Safety and Health Administration (Non-Mandatory Form) Form Approved OMB No. 1218-0072

Acrylic Resurfacer

Product No. C1300

SECTION I - Manufacturer / Product Information

Manufacturer's Name: ThorWorks Industries, Inc. Address: 2520 South Campbell Street Sandusky, Ohio 44870

Emergency Telephone No.: Chemtrec: 1-800-424-9300 **Telephone Number for Information:** 1-800-326-1994 **Date Prepared:** August 10, 2004

LEL: N/A

UEL: N/A

SECTION II - Chemical Identity Information						
Ingredient	CAS #	OSHA_PEL	ACGIH_TLV	Other Limits	Percent	
Texanol	25265-77-4	N/A	N/A			
Carbon Black	1333-86-4	3.5 mg/m3	3.5 mg/m3			

SECTION III - Physical / Chemical Characteristics

 Boiling Point: 100? Celsius (212? Fahrenheit)
 Specific Gravity (H2O = 1): 1.06

 Vapor Pressure (mm Hg): Nearly equal to water.
 Melting Point: N/A

 Vapor Density (AIR = 1): <1</td>
 Evaporation Rate (Butyl Acetate = 1): Approximately 1.8

 Solubility in Water: Easily dispersible in the liquid state.
 American and Odem Plack light odem

Appearance and Odor: Black liquid, mild odor.

SECTION IV - Fire and Explosion Hazard Data

Flash Point (Method Used): N/A Flammable Limits: N/A

Extinguishing Media: Foam, CO2, dry chemical, water fog, other.

Special Fire Fighting Procedures: Full protective equipment, including self-contained breathing apparatus to be worn. Water cool sealed containers in area of fire to prevent rupture due to steam generation.

Unusual Fire and Explosion Hazards: N/A

SECTION V - Reactivity Data

Stability:Unstable:Stable: XConditions to Avoid: Keep from freezing and extreme heat.Incompatibility (Materials to Avoid): Strong oxidizers.HazardousDecomposition or Byproducts: Combustion may yield fumes, smoke, carbon monoxide, carbon dioxide and other toxic pyrolysis products.Hazardous Polymerization:May Occur:Will Not Occur: XConditions to Avoid: N/A

SECTION VI - He	alth Hazard Da	ta						
Route(s) of Entry:	Inhalation? Yes	Skin Contact? No	Ingestion? Yes	Eye Contact? Yes				
Health Hazards (Acute an	nd Chronic):							
(Acute): Dizziness, weakness, nausea, headache.								
(Chronic): Gastrointestinal irritation – prolonged or repeated exposure to high vapor concentrations may								
cause damage to kidneys,	liver, lungs, blood	, or central nervous sys	stem. Repeated inge	estion may cause				
liver damage.								
Carcinogenicity:	NTP? No	IARC Monographs	? No OSHA	A Regulated? No				
Signs and Symptoms of E								
Inhalation: Vapor could of			at, dizziness, weak	ness and nausea.				
Ingestion: Can cause nausea, vomiting, diarrhea.								
Skin: Not easily absorbed – prolonged or repeated exposure may be mildly irritating to the skin. May cause								
allergic skin reactions in some people.								
Eye: Irritation from vapor								
Medical Conditions Generally Aggravated by Exposure: None known.								
Emergency and First Aid			· · · · · · · · · · · · · · · · · · ·					
Inhalation: Remove to fresh air and provide oxygen if breathing is difficult. If not breathing, give artificial								
resuscitation. IMMEDIATELY CALL A PHYSICIAN.								
Ingestion: If vomiting begins keep head below hips to avoid aspiration into lungs. DO NOT INDUCE								
VOMITING. Give victim a glass of water or milk. Never give anything by mouth to an unconscious								
person. CALL A PHYSICIAN OR POISON CONTROL CENTER IMMEDIATELY.								
Skin Contact: Wash area with soap and water. Remove contaminated clothing. IF IRRITATION OCCURS, CALL A PHYSICIAN.								
Eye Contact: Gently flush with large amounts water for at least 15 minutes or until eye is clear.								
IMMEDIATELY CALL A PHYSICIAN.								
SECTION VII - P	reconstions for S	ofo Hondling and	Uso					
				h 'm ant maatan'al (aan 1				
Steps to be taken in case material is released or spilled: Dike and contain spill with inert material (sand,								
sawdust, diamateous earth, etc.). Pump liquid into storage tanks. Remaining liquid may be taken up with inert materials. Place in closed container for proper disposal.								
Waste Disposal Method: Dispose of in accordance with Local, State, and Federal regulations.								
Precautions to Be Taken in Handling and Storage: Keep container closed and upright to prevent								
leakage. Avoid freezing or temperatures above 50? Celsius.								
Other Precautions: Do not take internally. Keep away from children. Avoid breathing vapors. For								
external use only.								

SECTION VIII - Control Measures

Respiratory Protection (Specify Type): None required if good ventilation is maintained. Otherwise use NIOSH approved respirator designed to remove particles and vapor.

Ventilation: Local Exhaust: Yes

Special: N/A **Other:** N/A

Mechanical (General): N/A Protective Gloves: Yes Eye

Eye Protection: Yes

Other Protective Clothing or Equipment: A rubber apron is recommended to protect clothing from splash during application.

Work/Hygienic Practices: Do not apply during or just before (within one hour) of rain to avoid contamination of runoff water. Wash hands before eating.

SECTION IX - Disclaimer

All information, recommendations, and suggestions concerning this product are based upon tests, literature references, and/or calculations, believed to be reliable. The manufacturer makes no guarantee, expressed or implied, as to the affect of use, or the safety and toxicity of the product. The information contained in this sheet cannot be taken as the sum total of all protective measures to be taken.