

H.M.I.S. RATING			
Health	1		
Flammability	0		
Reactivity	0		
Protective Equip.	Е		

# Material Safety Data Sheet – OSHA 174 Material Safety Data Sheet US Dep

May be used to comply with OSHA's Hazard communication Standard, 29 CFR 1910.1200. Standard must be consulted for specific requirements.

### **US Department of Labor**

Occupational Safety and Health Administration (Non-Mandatory Form) Form Approved OMB No. 1218-0072

# **ColorPlus Pigment Dispersion – Beige**

Product No. C1378

# SECTION I - Manufacturer / Product Information

Manufacturer's Name: ThorWorks Industries, Inc. Address: 2520 South Campbell Street Sandusky, Ohio 44870 **Emergency Telephone No.:** Chemtrec: 1-800-424-9300 **Telephone Number for Information:** 1-800-326-1994 **Date Prepared:** August 10, 2004

LEL: N/A

UEL: N/A

SECTION II - Chemical Identity Information						
Ingredient	CAS#	OSHA_PEL	ACGIH_TLV	Other Limits	Percent	
Titanium Dioxide	13463-67-7	15 mg/m3	10 mg/m3			
Iron Oxide	1332-37-2	10 mg/m3	5 mg/m3			

#### **SECTION III - Physical / Chemical Characteristics**

Boiling Point: 100? Celsius (212? Fahrenheit)Specific Gravity (H2O = 1): 2.01Vapor Pressure (mm Hg): Nearly equal to water.Melting Point: N/AVapor Density (AIR = 1): <1</td>Evaporation Rate (Butyl Acetate = 1): Approximately 1.8Solubility in Water: Easily dispersible in the liquid state.

Appearance and Odor: Beige liquid, mild odor.

#### SECTION IV - Fire and Explosion Hazard Data

Flash Point (Method Used): N/A Flammable Limits: N/A

**Extinguishing Media:** Foam, CO2, dry chemical, water fog, other.

**Special Fire Fighting Procedures:** Full protective equipment, including self-contained breathing apparatus to be worn. Water cool sealed containers in area of fire to prevent rupture due to steam generation.

Unusual Fire and Explosion Hazards: N/A

# **SECTION V - Reactivity Data**

Stability:Unstable:Stable: XConditions to Avoid: Keep from freezing and extreme heat.Incompatibility (Materials to Avoid): Strong oxidizers.HazardousDecomposition or Byproducts: Combustion may yield fumes, smoke, carbon monoxide, carbon dioxide and other toxic pyrolysis products.Hazardous Polymerization:May Occur:Will Not Occur: XConditions to Avoid: N/A

SECTION VI - Health Hazard Data								
Route(s) of Entry:	Inhalation? Yes	Skin Contact? No	Ingestion? Yes	Eye Contact? Yes				
Health Hazards (Acut	te and Chronic):							
(Acute): Dizziness, w	eakness, nausea, heada	che.						
(Chronic): Gastrointe	stinal irritation – proloi	nged or repeated expos	ure to high vapor c	oncentrations may				
cause damage to kidn	eys, liver, lungs, blood	, or central nervous sys	stem. Repeated ing	estion may cause				
liver damage.	-	-		-				
Carcinogenicity:	NTP? No	IARC Monographs	? No OSHA	A Regulated? No				
Signs and Symptoms	of Exposure:							
Inhalation: Vapor could cause headache, irritation to nose and throat, dizziness, weakness and nausea.								
Ingestion: Can cause nausea, vomiting, diarrhea.								
<b>Skin:</b> Not easily absorbed – prolonged or repeated exposure may be mildly irritating to the skin. May cause								
allergic skin reactions in some people.								
Eye: Irritation from va	por or liquid.							
Medical Conditions G	enerally Aggravated b	y Exposure: None know	wn.					
<b>Emergency and First</b>	Aid Procedures:							
<b>Inhalation:</b> Remove to fresh air and provide oxygen if breathing is difficult. If not breathing, give artificial								
resuscitation. IMMEDIATELY CALL A PHYSICIAN.								
Ingestion: If vomiting begins keep head below hips to avoid aspiration into lungs. DO NOT INDUCE								
VOMITING. Give victim a glass of water or milk. Never give anything by mouth to an unconscious								
person. CALL A PHYSICIAN OR POISON CONTROL CENTER IMMEDIATELY.								
Skin Contact: Wash area with soap and water. Remove contaminated clothing. IF IRRITATION								
OCCURS, CALL A PHYSICIAN.								
Eye Contact: Gently flush with large amounts water for at least 15 minutes or until eye is clear.								
IMMEDIATELY CALL A PHYSICIAN.								
<b>SECTION VII -</b>	Precautions for S	afe Handling and	Use					
	case material is relea			h inert material (sand,				
sawdust, diamateous earth, etc.). Pump liquid into storage tanks. Remaining liquid may be taken up with								
inert materials. Place in closed container for proper disposal.								
Waste Disposal Method: Dispose of in accordance with Local, State, and Federal regulations.								
Precautions to Be Taken in Handling and Storage: Keep container closed and upright to prevent								
leakage. Avoid freezing or temperatures above 50? Celsius.								

**Other Precautions:** Do not take internally. Keep away from children. Avoid breathing vapors. For external use only.

#### **SECTION VIII - Control Measures**

**Respiratory Protection** (Specify Type): None required if good ventilation is maintained. Otherwise use NIOSH approved respirator designed to remove particles and vapor.

Ventilation: Local Exhaust: Yes

**Special:** N/A **Other:** N/A

Mechanical (General): N/A Protective Gloves: Yes Eye

Eye Protection: Yes

**Other Protective Clothing or Equipment:** A rubber apron is recommended to protect clothing from splash during application.

**Work/Hygienic Practices:** Do not apply during or just before (within one hour) of rain to avoid contamination of runoff water. Wash hands before eating.

#### **SECTION IX - Disclaimer**

All information, recommendations, and suggestions concerning this product are based upon tests, literature references, and/or calculations, believed to be reliable. The manufacturer makes no guarantee, expressed or implied, as to the affect of use, or the safety and toxicity of the product. The information contained in this sheet cannot be taken as the sum total of all protective measures to be taken.