

1. PRODUCT NAME

ColorPave HD Clear Coat

2. MANUFACTURER

ThorWorks Industries, Inc.
 2520 S. Campbell St.
 Sandusky, OH 44870
 Phone: 800-326-1994
 Fax: 419-626-5477
 www.thorworks.com

Additional Plant Locations:
 SealMaster has a nationwide network of manufacturing and distribution facilities.

Phone 1-800-395-7325 or visit website at www.sealmaster.net to find the location near you.

3. PRODUCT DESCRIPTION & BENEFITS

ColorPave HD Clear Coat is a 100% acrylic, clear drying emulsion specifically formulated as a protective top coat for ColorPave HD color coatings. It provides additional protection against ultra violet rays, moisture, oil, gas, and chemical attack. ColorPave HD Clear Coat helps extend the service life of ColorPave HD color coatings.

Basic Uses: To help seal, protect, and extend the service life of ColorPave HD color coatings.

Composition: ColorPave HD Clear Coat is comprised of 100% acrylic emulsion resins, specialty surfactants, and water.

Sizes: ColorPave HD Clear Coat is available in 5 gallon pails.

Color: Dries clear.

Limitations: ColorPave HD Clear Coat shall not be applied when surface or ambient temperature is below 50°F. Do not apply if temperature is expected to drop below 50°F at any time within a 24 hour period after application.

4. Physical/Chemical Properties: ColorPave HD Clear Coat is a highly durable pavement coating that meets the following material requirements when tested in accordance with ASTM D1475,

ASTM D3960, ASTM D711, ASTM D2486, ASTM D4585, and ASTM D2243 (see chemical and physical analysis chart below).

Environmental Considerations: ColorPave HD Clear Coat is an environmentally friendly 100% acrylic emulsion coating containing less than 150 grams per liter volatile organic content (VOC).

5. INSTALLATION

Surface must be clean and free from all loose material, dirt, grease, and oil.

Methods: ColorPave HD Clear Coat shall be applied by spray, brush, or roller.

Mixing Procedures:

ColorPave HD Clear Coat is a ready to use product. Do not dilute. Stir material before applying.

Application Rate: Apply ColorPave HD Clear Coat at a rate of .04 gallon per square yard (approximately 200 square feet per gallon) in a single coat application.

Estimating Material Requirements: Typically, one gallon of ColorPave HD Clear Coat will cover approximately 200 square feet (22 square yards) per coat.

Precautions: Both surface and ambient temperature shall be a minimum of 50°F. Temperature shall

not drop below 50°F in a 24 hour period following application. New asphalt surfaces shall be completely free of oils prior to coating. Keep Out Of Reach Of Children. Do not store unopened drums or pails in freezing temperatures.

6. AVAILABILITY & COST

Availability: ColorPave HD Clear Coat is supported by a nationwide network of SealMaster manufacturing facilities along with a national network of qualified applicators.

Cost: Cost information can be obtained from a local ColorPave HD Clear Coat applicator. Contact SealMaster for the ColorPave HD Clear Coat representative in your area.

7. WARRANTY

SealMaster warrants that ColorPave HD Clear Coat meets the chemical composition and performance requirements set forth in section 4. Liability to the buyer or user of this product is limited to the replacement value of the product only.

8. MAINTENANCE

Periodic pavement sweeping will ensure optimum product service life.

Chemical & Physical Analysis

Material Type	100% Acrylic Emulsion
ASTM D1475 - Weight Per Gallon	8.5 lbs./gallon
ASTM D711 Dry To No Pick-Up Time	<60 min
ASTM D2486 Scrub Resistance	500 cycles minimum
ASTM D4585 Water Resistance, Cycles	8 minimum
ASTM D2243 Freeze Thaw Cycles	5 cycles minimum

ColorPave® HD Clear Coat

9. TECHNICAL SERVICES

Manufacturer: Complete product specifications, material safety data sheets, and technical assistance is available from SealMaster.

Professional Applicator: Your local ColorPave HD Clear Coat applicator is available to provide on-site inspections and recommendations to meet your specific needs.

Form No.: SMT-164
Revised: 7/04

Copyright © 2004, SealMaster
All rights reserved.

ThorWorks Industries, Inc.
2520 South Campbell St.
Sandusky, OH 44870

Phone: 1-800-326-1994
FAX: 1-419-626-5477

10. FILING SYSTEMS

- SealMaster Online Specification at www.sealmaster.net
- Complete SealMaster Product and Equipment Catalog Available

www.sealmaster.net

The statements made on this specification sheet are believed to be true and accurate and are intended to provide a guide for approved application practices. As workmanship, weather, construction, condition of pavement, tools utilized, and other variables affecting results are all beyond our control, the manufacturer warrants only that the material conforms to product specifications and any liability to the buyer or user of this product is limited to the replacement value of the product only. The manufacturer expressly disclaims any implied warranties of merchantability or fitness for a particular purpose. Warranty is void on multi-coat applications if material made by other manufacturers is used with this product.