



T/C White Line Paint

CMT - 50

Revised: 4/07

1. PRODUCT NAME:

T/C White Line Paint

2. MANUFACTURER:

ThorWorks Industries, Inc.
2520 S. Campbell St.
Sandusky, OH 44870
Phone: 800-395-7325
Fax: 419-626-5477
www.thorworks.com

Additional Plant Locations:

SealMaster has a nationwide network of manufacturing and distribution facilities.

Phone 1-800-395-7325 or visit www.sealmaster.net to find the location near you.

3. PRODUCT DESCRIPTION & BENEFITS:

T/C White Line Paint is a 100% acrylic emulsion paint.

Color: Available in white.

Uses: Line marking on tennis courts, running tracks, and other asphalt or concrete pavement surfaces.

4. SURFACE PREPARATION:

Pavement surface must be cleaned entirely of dust, dirt, debris and all loose material. If using T/C White Line Paint on a new, uncoated surface, allow adequate curing time before application.

5. MIXING PROCEDURES:

T/C White Line Paint can be rolled, brushed or sprayed with low pressure spraying equipment. To assure crisp lines, it is advisable to use a high quality tape to mask lines. Remove tape as soon as T/C White Line Paint has dried. T/C White Line Paint can be modified to match the exact texture of the court surface by adding 80 to 100 mesh silica sand.

6. IMPORTANT:

Stir before using. Temperatures must be above 50°F both during application and for a period of at least 24 hours after application. Do not apply if rain is imminent or forecast. Keep from freezing. Close container when not in use. On outdoor concrete surfaces, assure

adequate and functional perimeter drains as well as a sound vapor barrier beneath the slab.

7. DRYING TIME:

Thirty to sixty (30 to 60) minutes under optimum drying conditions. Indoor applications are substantially affected by temperature and available ventilation and will dry more slowly.

8. COVERAGE:

500 to 600 lineal feet of 2-inch line per gallon.

9. CAUTION:

Do not store in direct sunlight or where temperatures exceed 100°F. Do not apply if rain is imminent or forecast. Keep from freezing. Close container when not in use.

10. WARRANTY:

The statements made on this technical bulletin are believed to be true and accurate, and are intended to provide a guide for approved construction practices. Manufacturer does not make, nor does it authorize any agent or representative to make any warranty, express or implied, concerning this material as workmanship, weather, construction, equipment utilized and other variables affecting results are all beyond our control. Manufacturer warrants only that the material conforms to product specifications and any liability to the buyer or user of this product is limited to the replacement value of the product only. In no event shall Manufacturer be liable for any injury, loss or damage, either direct or incidental, special or consequential, however arising, in connection with material or

equipment furnished or work performed. Manufacturer shall not, in any manner, be liable for any defects, variations or change in condition in the substructure over which its products are installed.

Copyright© 2007,
ThorWorks Industries, Inc.
All rights reserved.

ThorWorks Industries, Inc.
P.O. Box 2277
Sandusky, OH 44870

Phone: 1-800-326-1994
FAX: 1-419-626-5477

www.sportmaster.net

T/C White Line Paint
CMT - 50

SportMaster
April 2007

SPORT SURFACING

Product Data:

Type	Acrylic Emulsion
Weight per gallon at 77°F.....	10.5 ± .5 lbs.
% Non Volatile Material.....	49 ± 2
Odor	Ammonia
Flammability.....	Non-Flammable
Flash Point.....	None
Storage Life	One Year